





# Electrical Accessories

## UniversalFilter Group

### UniversalFilter Group:801







Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for 80 fans: 8025/8038	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs



### UniversalFilter Group:802



Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for 92 fans: 9225/9238	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs







# Electrical Accessories

## UniversalFilter Group

### UniversalFilter Group:803







Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for 120 series fans: 11025/12025/12038	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs



### UniversalFilter Group:804



Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for 150/170 series fans: 15050/17238/17250/17150/12025/12038	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs







# Electrical Accessories

## UniversalFilter Group

### UniversalFilter Group:805



Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for: 17250/17150/17238/20060/22060/22580 axial fans	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs



### UniversalFilter Group:806



Technical data		
General Network Body Material	ABS Resin (Flammable, Ultraviolet Resistance)94V-O,UL Fire Line	
Filtration Material	Nylon Fiber Composite	
Filtration Pressure Loss	Initial 6.7mm End:20mm AQ	
Maximum wind speed	1.5M/SEC	
All ranges	50m³/MIN	
Preventive yield	AF186% (feed yeid:520g/m²) (JAPAN AIR FILTER INSTIUDE)	
General fan	Suitable for: 17250/17150/17238/20060/22060/22580/25489/28080 axial fans	
Waterproof rating	IP55	
Annex	Filter X 1pcs	Screw group X8 PCs

